



# Test Report: APV-25-24

---

25W Single Output Switching Power Supply

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

| NO | TEST ITEM                | SPECIFICATION                                   | TEST CONDITION  | RESULT                                 | VERDICT |
|----|--------------------------|---|---|--|---------|
| 1  | RIPPLE & NOISE           | V1 : 150 mVp-p (Max)                            | I/P : 230VAC<br>O/P : FULL LOAD<br>Ta : 25°C  | V1 : 60 mVp-p (Max)                    | P       |
| 2  | OUTPUT VOLTAGE TOLERANCE | V1 : 5 %~-5 % (Max)                             | I/P : 100 VAC / 264 VAC<br>O/P : FULL/ MIN LOAD<br>Ta : 25°C  | V1 : 1.246 %~-0.513 %                  | P       |
| 3  | LINE REGULATION          | V1 : 1 %~-1 % (Max)                             | I/P : 100 VAC ~ 264 VAC<br>O/P : FULL LOAD<br>Ta : 25°C   | V1 : 0.192 %~-0.075 %                  | P       |
| 4  | LOAD REGULATION          | V1 : 2 %~-2 % (Max)                             | I/P : 230 VAC<br>O/P : FULL ~MIN LOAD<br>Ta : 25°C  | V1 : 0.279 %~-0.206 %                  | P       |
| 5  | SET UP TIME              | 230VAC : 1500 ms (Max)<br>115VAC : 1500 ms(Max) | I/P : 230 VAC<br>I/P : 115 VAC<br>O/P : FULL LOAD<br>Ta : 25°C  | 230VAC/ 284.72 ms<br>115VAC/ 285.11 ms | P       |
| 6  | RISE TIME                | 230VAC : 30 ms (Max)<br>115VAC : 30 ms (Max)    | I/P : 230 VAC<br>I/P : 115 VAC<br>O/P : FULL LOAD<br>Ta : 25°C  | 230VAC/ 7.22 ms<br>115VAC/ 8.23 ms     | P       |
| 7  | HOLD UP TIME             | 230VAC : 20 ms (TYP)<br>115VAC : 12 ms (TYP)    | I/P : 230 VAC<br>I/P : 115 VAC<br>O/P : FULL LOAD<br>Ta : 25°C  | 230VAC/ 71.67 ms<br>115VAC/ 15.14 ms   | P       |
| 8  | OVER/UNDERSHOOT TEST     | < ± 5 %   | I/P : 230 VAC<br>O/P : FULL LOAD<br>Ta : 25°C   | TEST : < 5 %                           | P       |
| 9  | DYNAMIC LOAD             | V1 : 2400 mVp-p                                 | I/P : 230 VAC<br>(1).O/P : FULL /Min LOAD 90%DUTY/<br>1KHZ<br>(2).O/P : FULL /Min LOAD 50%DUTY/<br>120HZ<br>Ta : 25°C | (1) 220 mVp-p<br>(2) 608 mVp-p         | P       |

INPUT FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|-----------|---------------|----------------|--------|---------|
|----|-----------|---------------|----------------|--------|---------|

|   |                       |   |  |  |   |
|---|-----------------------|---|--|--|---|
| 1 | INPUT VOLTAGE RANGE   | 90VAC~264 VAC   | I/P:TESTING<br>O/P:FULL LOAD<br>Ta:25°C  | 87 V~ 264 V                                  | P |
|   |                       |   | (1)I/P: LOW-LINE-3V= 87 V<br>HIGH-LINE+15%= 300 V<br>O/P:FULL/MIN LOAD<br>ON: 30 Sec . OFF: 30 Sec 10MIN<br>(2) I/P:230VAC<br>ON: 0.5 Sec . OFF: 0.5 Sec 20MIN<br>(AC POWER ON/OFF NO DAMAGE ) | TEST:<br>(1) OK<br>(2) OK                    |   |
| 2 | INPUT FREQUENCY RANGE | 47HZ ~63 HZ<br>NO DAMAGE OSC  | I/P : 90 VAC ~ 264 VAC<br>O/P : FULL~MIN LOAD<br>Ta : 25°C   | TEST : OK                                    | P |
| 3 | EFFICIENCY            | 83 % (TYP)  | I/P : 230 VAC<br>O/P : FULL LOAD<br>Ta : 25°C  | 85.31 %                                      | P |
| 4 | INPUT CURRENT         | 230V/ 0.4 A (TYP)<br>115V/ 0.8 A (TYP)                                    | I/P : 230 VAC<br>I/P : 115 VAC<br>O/P : FULL LOAD<br>Ta : 25°C   | I = 0.291 A/ 230 VAC<br>I = 0.446 A/ 115 VAC | P |
| 5 | INRUSH CURRENT        | 230V/ 45 A (TYP)<br>Twidth =310 us measured at 50%<br>Ipeak<br>COLD START | I/P : 230 VAC<br>O/P : FULL LOAD<br>Ta : 25°C  | I = 36.8 A/ 230 VAC<br>Twidth =247 us        | P |
| 6 | LEAKAGE CURRENT       | < 0.25 mA / 240 VAC   | I/P : 240 VAC<br>O/P : Min LOAD<br>Ta : 25°C   | L-CASE : 0.003 mA<br>N-CASE : 0.003 mA       | P |

### PROTECTION FUNCTION TEST

| NO | TEST ITEM               | SPECIFICATION                          | TEST CONDITION  | RESULT  | VERDICT |
|----|-------------------------|--|---|---|---------|
| 1  | OVER LOAD PROTECTION    | >105%                                  | I/P : 230 VAC<br>I/P : 115 VAC<br>O/P : TESTING<br>Ta : 25°C  | 140.95 %/ 230 VAC<br>140.05 %/ 115 VAC<br>Hiccup mode                               | P       |
| 2  | OVER VOLTAGE PROTECTION | CH1 : 27 V ~ 32.4 V                    | I/P : 230 VAC<br>I/P : 115 VAC<br>O/P : MIN LOAD<br>Ta : 25°C | 30.2 V/ 230 VAC<br>30.2 V/ 115 VAC<br>Shut down o/p voltage, re-power on to recover | P       |
| 3  | SHORT PROTECTION        | SHORT EVERY OUTPUT<br>1 HOUR NO DAMAGE | I/P : 264 VAC<br>O/P : FULL LOAD<br>Ta : 25°C                 | NO DAMAGE<br>Hiccup mode  | P       |

### COMPONENT STRESS TEST

| NO | TEST ITEM        | SPECIFICATION | TEST CONDITION              | RESULT    | VERDICT |
|----|------------------|---------------|-----------------------------|-----------|---------|
| 1  | Power Transistor | Q1 Rated :    | I/P : High-Line +3V = 267 V | (1) 494 V | P       |

|   |                                   |  |  |  |   |
|---|-----------------------------------|--|--|--|---|
|   | (D to S) or (C to E) Peak Voltage | NDF06N60ZG : 600 V/ 6.0 A                | O/P : (1)Full Load Turn on<br>(2) Output Short<br>(3)Full load continue<br>Ta : 25°C   | (2) 540 V<br>(3) 486 V                 |   |
| 2 | Diode Peak Voltage                | D100 Rated :<br>FMX-12SL:200V/ 10 A      | I/P : High-Line +3V = 267 V<br>O/P : (1)Full Load Turn on<br>(2)Output Short<br>(3)Full load continue<br>Ta : 25°C                           | (1) 157 V<br>(2) 143 V<br>(3) 155 V    | P |
| 3 | Input Capacitor Voltage           | C5 Rated :<br>47u/420V 105°C 18*20 KM    | I/P : High-Line +3V = 267 V<br>O/P : (1)Full Load Turn on /Off<br>(2) Min load Turn on /Off<br>(3)Full Load /Min load<br>Change<br>Ta : 25°C | (1) 390 V<br>(2) 380 V<br>(3) 378 V    | P |
| 4 | Control IC Voltage Test           | U 1 Rated :<br>NCP1200D100R2G: 16V (MAX) | I/P : High-Line +3V = 267 V<br>O/P : (1)Full Load Turn on /Off<br>(2) Min load Turn on /Off<br>(3)Full Load /Min load<br>Change<br>Ta : 25°C | (1) 11.8 V<br>(2) 11.8 V<br>(3) 11.8 V | P |

## ■ SAFETY & E.M.C. TEST

### SAFETY TEST

| NO | TEST ITEM            | SPECIFICATION          | TEST CONDITION                        | RESULT                              | VERDICT |
|----|----------------------|------------------------|---------------------------------------|-------------------------------------|---------|
| 1  | WITHSTAND VOLTAGE    | I/P-O/P : 3 KVAC/min   | I/P-O/P : 3.6 KVAC/min<br>Ta : 25°C   | I/P-O/P : 0.895 mA<br><br>NO DAMAGE | P       |
| 2  | ISOLATION RESISTANCE | I/P-O/P : 500VDC>100MΩ | I/P-O/P : 500 VDC<br>Ta : 25°C/70% RH | I/P-O/P : >9999 MΩ<br><br>NO DAMAGE | P       |

### E.M.C TEST

| NO | TEST ITEM  | SPECIFICATION  | TEST CONDITION  | RESULT                        | VERDICT |
|----|------------|--|---|-------------------------------|---------|
| 1  | HARMONIC   | EN61000-3-2<br>CLASS A                                 | I/P:230VAC/240VAC/220VAC50HZ<br>O/P:100% LOAD<br>CLASS A<br>Ta:25°C | PASS                          | P       |
| 2  | CONDUCTION | EN55022<br>CLASSB                                      | I/P: 230 VAC (50HZ)/115V[60HZ]<br>O/P:FULL LOAD<br>Ta:25°C          | PASS<br>Test by certified Lab | P       |
| 3  | RADIATION  | EN55022<br>CLASSB                                      | I/P: 230 VAC (50HZ)/115V[60HZ]<br>O/P: FULL LOAD<br>Ta:25°C         | PASS<br>Test by certified Lab | P       |
| 4  | E.S.D      | EN61000-4-2<br>LIGHT INDUSTRY<br>AIR:8KV / Contact:4KV | I/P: 230 VAC/50HZ<br>O/P:FULL LOAD<br>Ta:25°C                       | CRITERIA A                    | P       |

|   |   |   |   |            |   |
|---|---|---|---|------------|---|
| 5 | E.F.T                                       | EN61000-4-4<br>LIGHT INDUSTRY<br>INPUT: 1KV | I/P: 230 VAC/50HZ<br>O/P:FULL LOAD<br>Ta:25°C | CRITERIA A | P |
| 6 | SURGE                                       | IEC61000-4-5<br>INDUSTRY<br>L-N :2KV        | I/P: 230 VAC/50HZ<br>O/P:FULL LOAD<br>Ta:25°C | CRITERIA A | P |
| 7 | Test by certified Lab & Test Report Prepare |   |   |            |   |

## RELIABILITY TEST

### ENVIRONMENT TEST

| NO | TEST ITEM   | SPECIFICATION   | TEST CONDITION   | RESULT            | VERDICT |
|----|---|---|--|-------------------|---------|
| 1  | TEMPERATURE RISE TEST   | MODEL : APV-25-24<br>1. ROOM AMBIENT BURN-IN : 2.5 HRS<br>I/P : 230VAC O/P : FULL LOAD Ta=30.2 °C<br>2. HIGH AMBIENT BURN-IN : 3.5 HRS<br>I/P : 230VAC O/P : FULL LOAD Ta=43.4 °C |  |                   | P       |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
|    |   |   |  |                   |         |
| 2  | OVER LOAD BURN-IN TEST  | NO DAMAGE<br>1 HOUR ( MIN )   | I/P : 230 VAC<br>O/P : 140 % LOAD<br>Ta : 25°C                     | TEST : OK         | P       |
| 3  | LOW TEMPERATURE<br>TURN ON TEST                                   | TURN ON AFTER 2 HOUR  | I/P : 264VAC/100VAC<br>O/P : FULL LOAD<br>Ta= -30°C                | TEST : OK         | P       |
| 4  | HIGH HUMIDITY<br>HIGH TEMPERATURE<br>HIGH VOLTAGE<br>TURN ON TEST | AFTER 12 HOURS<br>IN CHAMBER ON<br>CONTROL 40 °C<br>NO DAMAGE   | I/P : 264 VAC<br>O/P : FULL LOAD<br>Ta= 40 °C<br>HUMIDITY= 95 %R.H | TEST : OK         | P       |
| 5  | TEMPERATURE<br>COEFFICIENT  | ± 0.03 %(0~50°C)  | I/P : 230 VAC<br>O/P : FULL LOAD                                   | ± 0.005 %(0~50°C) | P       |

|    |                             |   |   |   |
|----|-----------------------------|---|---|---|
| 6  | STORAGE TEMPERATURE TEST    | <ol style="list-style-type: none"> <li>1. Thermal shock Temperature : -45°C~ +85°C</li> <li>2. Temperature change rate : 25°C / MIN</li> <li>3. Dwell time low and high temperature : 30 MIN/EACH</li> <li>4. Total test cycle : 5 CYCLE</li> <li>5. Input/Output condition : STATIC</li> </ol>   | OK  | P |
| 7  | THERMAL SHOCK TEST          | <ol style="list-style-type: none"> <li>1. Thermal shock Temperature : -35°C~ +45°C</li> <li>2. Temperature change rate : 25°C / MIN</li> <li>3. Dwell time low and high temperature : 30 MIN/EACH</li> <li>4. Total test cycle : 10 CYCLE</li> <li>5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST<br/>turn on 58sec ; turn off 2sec</li> </ol> | OK  | P |
| 8  | VIBRATION TEST              | <p>1 Carton &amp; 1 Set</p> <ol style="list-style-type: none"> <li>(1) Waveform : Sine Wave</li> <li>(2) Frequency : 10~500Hz</li> <li>(3) Sweep Time : 12min/sweep cycle</li> <li>(4) Acceleration : 2G</li> <li>(5) Test Time : 72min in each axis (X.Y.Z)</li> <li>(6) Ta : 25°C</li> </ol>  | TEST : OK   | P |
| 9  | CAPACITOR LIFE CYCLE        | <p>APV-25-24 :SUPPOSE C106 IS THE MOST CRITICAL COMPONENT</p> <ol style="list-style-type: none"> <li>(1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME</li> <li>(2) I/P : 230VAC O/P : FULL LOAD Ta=40 °C LIFE TIME</li> <li>(3) I/P : 230VAC O/P : 75% LOAD Ta=40 °C LIFE TIME</li> </ol>  | <ol style="list-style-type: none"> <li>(1) 63873.5 HRS</li> <li>(2) 21827.5 HRS</li> <li>(3) 29173.3 HRS</li> </ol> | P |
| 10 | MTBF                        | <p>Conducted by Parts Stress Analysis Prediction</p> <p>5489.6K hrs min. Telcordia SR-332 (Bellcore) ; 600K hrs min. MIL-HDBK-217F (25°C)</p>   |   | P |
| 11 | DMTBF/Accelerated Life Test | <p>Demonstration Mean Time Between Failure(Expected Life) :</p> <p>20,000 hours @ Tcase 70°C ; 50,000 hours @ Tcase 55°C</p>  |   | P |

| DATE       | SAMPLE         | TEST RESULT | TESTER | APPROVAL |
|------------|----------------|-------------|--------|----------|
| 2012/05/30 | PRODUCT SAMPLE | PASS        | ZOULF  | HOWAY    |

2009/08/04 A50-F023