



# Test Report : DKM10B-05

---

10W 1"x1" Package DC-DC Regulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5 % ~ +1.5 % (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	V1 +0.30 % V2 +0.68 %	P
2	RIPPLE & NOISE	50 mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	V1 23.8 mV V2 20.9 mV	P
3	LINE REGULATION	-0.2% ~ +0.2% (Max)	I/P:18VDC~36VDC O/P:FULL LOAD Ta:25°C	V1 -0.020% ~ +0.020% V2 -0.020% ~ +0.001%	P
4	LOAD REGULATION	-1% ~ +1% (Max)	I/P:24VDC O/P:NO LOAD-FULL LOAD Ta:25°C	V1 -0.090% ~ +0.090% V2 -0.109% ~ +0.109%	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	85 % (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	85.6 %	P
2	DC CURRENT	490 mA / FULL LOAD (Max) 25 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	489 mA / FULL LOAD 16 mA / NO LOAD	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~140% LOAD (Typ)	I/P:12VDC O/P:TESTING Ta:25°C	128%	P
2	INPUT UNDER VOLTAGE LOCKOUT	Power Up 17V (Typ) Power Down 16V (Typ)	I/P:TESTING O/P: 10% LOAD Ta:25°C	Vin turn off : 15.96V Vin turn on : 17.10V	P
3	SHORT PROTECTION	CONTINUOUS	I/P:18VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE OK	P

**CONTROL FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C >5.5Vdc~75Vdc or open Power off : R.C <1.2Vdc or short	I/P:24VDC O/P:10% LOAD Ta:25°C	OK	P

**SAFETY TEST**
**SAFETY TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

**RELIABILITY TEST**
**ENVIRONMENT TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 12HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 12HRS I/P:24VDC O/P:FULL LOAD Ta=71°C	<table border="1" data-bbox="651 1055 1147 1149"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>31.0°C</td> <td>77.0°C</td> </tr> </tbody> </table>	NO	Position	1	2	1	CASE	31.0°C	77.0°C		P
NO	Position	1	2										
1	CASE	31.0°C	77.0°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P								

**OTHER**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.859 M.T.B.F : 1,164,436 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ALROY WANG	VINCENT ZENG