



# Test Report: HBG-160P-60

---

160W Constant Voltage + Constant Current LED Driver

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 300 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 60 mVp-p (Max)	P
2	CONSTANT CURRENT REGION	CH1: 36 V ~ 60 V	I/P : 230VAC O/P : CV MODE Ta : 25°C	O/P= 36V : 2.616 A O/P= 60V : 2.626 A	P
3	CURRENT ADJUST RANGE	CH1: 1.6 A ~ 2.6 A	I/P : 230VAC I/P : 115VAC O/P : CV MODE Ta : 25°C	1.447 A ~ 2.892 A /230VAC 1.448 A ~ 2.592 A /115VAC	P
4	OUTPUT VOLTAGE TOLERANCE	V1 : 2%~ -2% (Max)	I/P : 100 VAC / 305 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.645 %~ -0.208 %	P
5	LINE REGULATION	V1 : 0.5%~ -0.5% (Max)	I/P : 100 VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ 0 %	P
6	LOAD REGULATION	V1 : 1%~ -1% (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.041 %~ -0.051 %	P
7	SET UP TIME	230VAC : 500 ms (Max) 115VAC : 2500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 229.848 ms 115VAC/ 420.686 ms	P
8	RISE TIME	230VAC : 200 ms (Max) 115VAC : 200 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 34.95 ms 115VAC/ 34.70 ms	P
9	HOLD UP TIME	230VAC : 12 ms (TYP) 115VAC : 12 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 22.56 ms 115VAC/ 22.67 ms	P
10	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
11	DYNAMIC LOAD	V1 : 6000 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 350 mVp-p (2) 2470 mVp-p	P

12	DIMMING TEST (B-TYPE)	<p>SPEC: *Output constant current level can be adjusted by applying one of the three methodologies between DIM+ and DIM-: 1 ~ 10Vdc, or 10V PWM signal or resistance.</p> <p>*Reference resistance value for output current adjustment (Typical)</p> <table border="1" data-bbox="311 392 1364 504"> <tr> <th>Resistance value</th> <td>10K</td><td>20K</td><td>30K</td><td>40K</td><td>50K</td><td>60K</td><td>70K</td><td>80K</td><td>90K</td><td>100K</td> </tr> <tr> <th>Output current</th> <td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td> </tr> </table> <p>*1 ~ 10V dimming function for output current adjustment (Typical)</p> <table border="1" data-bbox="311 537 1364 649"> <tr> <th>Dimming value</th> <td>1V</td><td>2V</td><td>3V</td><td>4V</td><td>5V</td><td>6V</td><td>7V</td><td>8V</td><td>9V</td><td>10V</td> </tr> <tr> <th>Output current</th> <td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td> </tr> </table> <p>*10V PWM signal for output current adjustment (Typical) Frequency range : 100Hz~3KHz</p> <table border="1" data-bbox="311 683 1364 817"> <tr> <th>Duty value</th> <td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td> </tr> <tr> <th>Output current</th> <td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td> </tr> </table> <p>TEST RESULT: I/P : 230 VAC ; Ta : 25°C</p> <table border="1" data-bbox="311 907 1396 1467"> <tr> <td rowspan="3">1</td> <td>Resistance value</td> <td>10K</td><td>20K</td><td>30K</td><td>40K</td><td>50K</td><td>60K</td><td>70K</td><td>80K</td><td>90K</td><td>100K</td> </tr> <tr> <td>Output current</td> <td>0.244A</td><td>0.511A</td><td>0.781A</td><td>1.045A</td><td>1.312A</td><td>1.582A</td><td>1.853A</td><td>2.125A</td><td>2.399A</td><td>2.644A</td> </tr> <tr> <td>%</td> <td>9.38%</td><td>19.65%</td><td>30.04%</td><td>40.19%</td><td>50.46%</td><td>60.85%</td><td>71.27%</td><td>81.73%</td><td>92.27%</td><td>101.7%</td> </tr> <tr> <td rowspan="3">2</td> <td>Dimming value</td> <td>1V</td><td>2V</td><td>3V</td><td>4V</td><td>5V</td><td>6V</td><td>7V</td><td>8V</td><td>9V</td><td>10V</td> </tr> <tr> <td>Output current</td> <td>0.249A</td><td>0.510A</td><td>0.770A</td><td>1.029A</td><td>1.287A</td><td>1.548A</td><td>1.806A</td><td>2.069A</td><td>2.330A</td><td>2.588A</td> </tr> <tr> <td>%</td> <td>9.58%</td><td>19.62%</td><td>29.62%</td><td>39.58%</td><td>49.50%</td><td>59.54%</td><td>69.46%</td><td>79.58%</td><td>89.62%</td><td>99.54%</td> </tr> <tr> <td rowspan="3">3</td> <td>Duty value</td> <td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td> </tr> <tr> <td>Output current</td> <td>0.270A</td><td>0.530A</td><td>0.794A</td><td>1.049A</td><td>1.307A</td><td>1.565A</td><td>1.823A</td><td>2.083A</td><td>2.342A</td><td>2.583A</td> </tr> <tr> <td>%</td> <td>10.38%</td><td>20.38%</td><td>30.54%</td><td>40.35%</td><td>50.27%</td><td>60.19%</td><td>70.12%</td><td>80.12%</td><td>90.08%</td><td>99.35%</td> </tr> </table>	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	0.244A	0.511A	0.781A	1.045A	1.312A	1.582A	1.853A	2.125A	2.399A	2.644A	%	9.38%	19.65%	30.04%	40.19%	50.46%	60.85%	71.27%	81.73%	92.27%	101.7%	2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	0.249A	0.510A	0.770A	1.029A	1.287A	1.548A	1.806A	2.069A	2.330A	2.588A	%	9.58%	19.62%	29.62%	39.58%	49.50%	59.54%	69.46%	79.58%	89.62%	99.54%	3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	0.270A	0.530A	0.794A	1.049A	1.307A	1.565A	1.823A	2.083A	2.342A	2.583A	%	10.38%	20.38%	30.54%	40.35%	50.27%	60.19%	70.12%	80.12%	90.08%	99.35%	P
Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																																																																																																																																																																	
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																	
Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																																																																																																																																																																	
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																	
Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																	
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																	
1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																																																																																																																																																																
	Output current	0.244A	0.511A	0.781A	1.045A	1.312A	1.582A	1.853A	2.125A	2.399A	2.644A																																																																																																																																																																
	%	9.38%	19.65%	30.04%	40.19%	50.46%	60.85%	71.27%	81.73%	92.27%	101.7%																																																																																																																																																																
2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																																																																																																																																																																
	Output current	0.249A	0.510A	0.770A	1.029A	1.287A	1.548A	1.806A	2.069A	2.330A	2.588A																																																																																																																																																																
	%	9.58%	19.62%	29.62%	39.58%	49.50%	59.54%	69.46%	79.58%	89.62%	99.54%																																																																																																																																																																
3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																
	Output current	0.270A	0.530A	0.794A	1.049A	1.307A	1.565A	1.823A	2.083A	2.342A	2.583A																																																																																																																																																																
	%	10.38%	20.38%	30.54%	40.35%	50.27%	60.19%	70.12%	80.12%	90.08%	99.35%																																																																																																																																																																
9	DALI DIMMING OPERATION (primary side for DA-Type)	<p>※DALI Interface          ·Apply DALI signal between DA+ and DA-.          ·DALI protocol comprises 16 groups and 64 addresses.          ·First step is fixed at 8% of output.</p> <p>I/P : 230 VAC          O/P : DIMMING TEST          Ta : 25°C          TEST RESULT : OK</p>																																																																																																																																																																									

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC~305 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	87 V~305V	P
			I/P : LOW-LINE-3V=97 V HIGH-LINE=305 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN ( AC POWER ON/OFF NO DAMAGE )	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 305 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.98 / 115 VAC(TYP) 0.92 / 277 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.971 / 230 VAC PF= 0.996 / 115 VAC PF= 0.947 / 277 VAC	P
4	EFFICIENCY	93.5 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	93.65 %	P
5	INPUT CURRENT	230V/ 0.78 A (TYP) 115V/ 1.70 A (TYP) 277V/ 0.70 A (TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	I = 0.748 A/ 230 VAC I = 1.494 A/ 115 VAC I = 0.635 A/ 277 VAC	P
6	INRUSH CURRENT	230V/ 65 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 55.65 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.75 mA / 277 VAC	I/P : 277 VAC O/P : Min LOAD Ta : 25°C	L-CASE : 0.3277 mA N-CASE : 0.3394 mA	P
8	TOTAL HARMONIC DISTORTION	Total harmonic distortion will be lower than 20% when output loading is 60% or higher at 115VAC/230VAC	I/P : 115VAC I/P : 230VAC O/P : 60% LOAD	THD : 8.33%/115VAC THD : 12.58%/230VAC	P
		Total harmonic distortion will be lower than 20% when output loading is 75% or higher at 277VAC	I/P : 277VAC O/P : 75% LOAD	THD : 13.71%/277VAC	

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95 % ~ 108 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	100.98 %/ 230 VAC 101.04 %/ 115 VAC Constant current limiting, recovers automatically after fault condition is removed.	P
2	OVER VOLTAGE PROTECTION	CH1 : 65 V ~ 75 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	70.1 V/ 230 VAC 70.1 V/ 115 VAC Shut down o/p voltage with auto-recovery or re-power on to recover	P
3	OVER TEMPERATURE PROTECTION	NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage, recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed.	P

**COMPONENT STRESS TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor ( D to S) or (C to E) Peak Voltage	Q6 Rated : 600V/11A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 476 V (2) 450 V (3) 456 V	P
2	Diode Peak Voltage	D100 Rated : 150V/30A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 132 V (2) 11.2 V (3) 133 V	P
3	Input Capacitor Voltage	C5 Rated : 82u/450V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 446 V (2) 442 V (3) 442 V	P
4	Control IC Voltage Test	U 2 Rated : 16V (MAX)	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 13.9 V (2) 13.8 V (3) 13.9 V	P
5	Power Transistor ( D to S) or (C to E) Peak Voltage	Q1 Rated : 600V/16A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 494 V (2) 454 V (3) 470 V	P

■ SAFETY & E.M.C. TEST

**SAFETY TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min I/P-FG : 2.0 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 4.2 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 2.987 mA I/P-FG : 2.838 mA O/P-FG : 3.672 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C/70% RH	I/P-O/P : >9999 MΩ I/P-FG : >9999 MΩ O/P-FG : >9999 MΩ NO DAMAGE	P

**E.M.C TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS C	I/P:220VAC/230VAC/240VAC50HZ O/P:100%,75%,60%LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P:FULL/65% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P: FULL/65% LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N- EARTH:4KKV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ **RELIABILITY TEST**

**ENVIRONMENT TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	MODEL : HBG-160P-48 1. ROOM AMBIENT BURN-IN : 1.0 HRS I/P : 230VAC O/P : 95% LOAD Ta=31.3 °C 2. HIGH AMBIENT BURN-IN : 2.0 HRS I/P : 230VAC O/P : 95% LOAD Ta=48.3 °C			P
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 95 % LOAD Ta= -45/-35°C	TEST : OK	P
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 45 °C NO DAMAGE	I/P : 305 VAC O/P : 95% LOAD Ta= 45 °C HUMIDITY= 95 %R.H	TEST : OK	P
4	TEMPERATURE COEFFICIENT	±0.03 %(0~45°C)	I/P : 230 VAC O/P : 95% LOAD	±0.005 %(0~45°C)	P
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C ~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C ~ +50°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	P

7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
8	CAPACITOR LIFE CYCLE	HBG-160P-48:SUPPOSE C102 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=45 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=45 °C LIFE TIME	(1) 430372 HRS (2) 161982 HRS (3) 209540 HRS	P
9	MTBF	Conducted by Parts Stress Analysis Prediction 2612.1K hrs min. Telcordia SR-332 (Bellcore) ; 195.6K hrs min. MIL-HDBK-217F (25°C)		P
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 50,000 hours @ Ta 45°C		P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	ZHANGZJ/ZHOUB	SKY	LIUWY

2009/08/04 A50-G058