



Declaration of Conformity

For the following equipment:				
Product Name: Switching Power Supply				
Model Designation: HRP-300N3-Z (Z=12,24,36,48)				
is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied :				
RoHS Directive (2011/65/EU)、(EU)2015/863				
Low Voltage Directive (2014/35/EU):				
EN 62368-1:2014+A11	TUV certificate No: R50427032			427032
Electromagnetic Compatibility Directive (2014/30/EU): EMI (Electro-Magnetic Interference) Conducted emission / Radiated emission EN 55032:2015+A11:2020 Class B				
Harmonic current	EN IEC 61000-3-2:2019			
Voltage flicker	EN 61000-3-3:2013+A1:20)19		
EMS (Electro-Magnetic Susceptibility)				
EN 55024:2010+A1:2015	EN 55035:2017+A11:2020	EN IEC 61000-6	5-2:2019	
ESD air	EN 61000-4-2:2009	Le	evel 3	8KV
ESD contact	EN 61000-4-2:2009	Le	evel 2	4KV
RF field susceptibility	EN IEC 61000-4-3:2020	Le	evel 3	10V/m
EFT bursts	EN 61000-4-4:2012	Le	evel 3	2KV/5KHz
Surge susceptibility	EN 61000-4-5:2014+A1:20)17 Le	evel 4	2KV/Line-Line
Surge susceptibility	EN 61000-4-5:2014+A1:20)17 Le	evel 4	4KV/Line-Earth

Note:

A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure.

For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies" (as available on http://www.meanwell.com)" and TDF (Technical Documentation File).

This Declaration is effective from serial number SC2xxxxxxx

Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

Conducted susceptibility

Magnetic field immunity

Voltage dip, interruption

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

EN 61000-4-6:2014

EN 61000-4-8:2010

residual voltage for 250 cycles

(Manufacturer Address)

Aries Jian/ Director, Group R&D:

(Name / Position)

(Signature) ries

Alex Tsai/Director, Product Strategy Center (Name / Position)

10V

30A/m

Level 3

Level 4

EN IEC 61000-4-11:2020 <5% residual voltage for 0.5 cycles ,70% residual voltage for 25 cycles , <5%

(Signature)

Taiwan

Jan. 10th, 2022 (Date)

(Place)

Version: 0