# **CERTIFICATE**

Issued to: Applicant:

MEAN WELL Enterprises Co., Ltd. No.28, Wuquan 3rd Rd, Wugu District 24891 New Taipei City, Taiwan Licensee:

MEAN WELL Enterprises Co., Ltd. No.28, Wuquan 3rd Rd, Wugu District 24891 New Taipei City, Taiwan

Product : Independent LED driver

Trade name(s) : MEAN WELL

Type(s)/model(s) : HVGC-65-XY (X=350, 500,700,1050, Y= A, B, D, AB)

The product and any acceptable variation thereto as specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of

- a type test according to EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017, EN 61347-1:2015, EN 61347-1:2015/A1:2021 and EN IEC 62384:2020
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 2175773

DEKRA hereby grants the right to use the ENEC certification mark

The ENEC certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the ENEC certification agreement.

This certificate is issued on 26 March 2023 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 35-103787/REV.1

DEKRA Certification B.V.

B.T.M. Holtus Managing Director

K. Lin /

Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE DUTCH ACCREDITATION COUNCIL







## SPECIFICATION OF THE CERTIFIED PRODUCT

Product data

Product : Independent LED driver

Trade name(s) : MEAN WELL

Type(s)/model(s) : HVGC-65-1050A, HVGC-65-1050AB, HVGC-65-1050B,

HVGC-65-1050D, HVGC-65-350A, HVGC-65-350AB, HVGC-65-350B, HVGC-65-350D, HVGC-65-500A, HVGC-65-500AB, HVGC-65-500B, HVGC-65-700A, HVGC-65-700AB, HVGC-65-700B and

HVGC-65-700D

Rated input voltage : 200-250 V~ Rated frequency : 50/60 Hz Power factor : 0,95 Ambient temperature (ta) : 55 °C Max. case temperature (tc) : 80 °C Class of insulation : Class I

Description : Thermal, short-circuit and overload protection

with MM signs

#### **TESTS**

**Test requirements** 

EN 61347-2-13:2014

EN 61347-2-13:2014/A1:2017

EN 61347-1:2015

EN 61347-1:2015/A1:2021

EN IEC 62384:2020

## Test result

The test results are laid down in DEKRA test file 438340900, 490032100.

## Additional information

This certificate replaces certificate No. 35-103787 which we hereby declare invalid.

The list of components is laid down in test report 4900321.50, 4383409.50.

## Conclusion

The examination proved that all requirements were met.

# **Factory location**

MEAN WELL (GUANGZHOU) Electronics Co., Ltd. No.11 Jingu South Road, Huadu District, 510890 Guangzhou Guangdong, China



Trade name(s) : MEAN WELL stands for



# **Model list:**

Model No	Input	Input	Output voltage	Output	Max.			
	voltage	current (A)	(V dc)	current	Output			
	(V)			(mA)	power (W)			
HVGC-65-350Y	200-250	0,39	Max 186	350	65,1			
HVGC-65-500Y	200-250	0,39	Max 130	500	65,0			
HVGC-65-700Y	200-250	0,39	Max 93	700	65,1			
HVGC-65-1050Y	200-250	0,39	Max 62	1050	65,1			
Remark: letter "Y" in model name can be A, B, AB, D								

# **Model Encoding:**

A: Constant current level can be adjusted through internal potentiometer.

B: Constant current level adjustable through output cable with 0-10 Vdc or 10 V PWM signal or resistance.

AB: Constant current level can be adjusted through internal potentiometer or output cable with 0-10 Vdc or 10 V PWM signal or resistance.

D: Smart timer dimming.

## **Model difference:**

Function mode	Main PCB	Dimming PCB	Dimming/DA wire	Front cover (with or without plastic cap)	IP
А	Same	Without	Without	With	65
В	Same	B type	With	Without	67
AB	Same	B type	With	With	65
D	Same	D type	Without	Without	67