



# Test Report: NID35-24

---

35W DC-DC Non-isolated Regulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST


ENVIRONMENT TEST

## DESIGN VERIFY TEST


### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OUTPUT VOLTAGE TOLERANCE (Max)	V1: -2%~2%	I/P: 30 VDC /53VDC O/P:FULL/ MIN. LOAD Ta:25°C	V1: -0.03%~0.01%
2	LINE REGULATION (Max)	V1: -0.5%- 0.5%	I/P: 30VDC /53 VDC O/P:FULL LOAD Ta:25°C	V1:-0.01%~0.01%
3	LOAD REGULATION (Max)	V1: -0.5%-0.5%	I/P: 48 VDC O/P:FULL -MIN LOAD Ta:25°C	V1:-0.03%~0.01%
4	OVER/UNDERSHOOT TEST	< ±5%	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	TEST: 2.1%
5	RIPPLE & NOISE (Max)	V1: 200mVp-p	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	V1:117mVp-p

high frequency :




low frequency :




6	DYNAMIC LOAD	V1: 1500mVp-p	I/P: 48 VDC O/P: (1)FULL /50% LOAD 50%DUTY / 120HZ (2)FULL /50% LOAD 50%DUTY / 1KHZ Ta:25°C	960mVp-p 870mVp-p
---	--------------	---------------	---	----------------------

FULL /50% LOAD 50%DUTY / 120HZ




FULL /50% LOAD 50%DUTY / 1KHZ



INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	30VDC-53VDC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	26.9V~ 56V
			I/P: LOW-LINE-0.2= 29.8V HIGH-LINE+3V= 56V O/P: FULL/MIN LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec . OFF: 30 Sec 10MIN (POWER ON/OFF NO DAMAGE)	TEST: OK
2	INPUT CURRENT(TYP)	FULL LOAD: 840mA NO LOAD: 50mA	I/P: 48 VDC O/P: FULL LOAD O/P: NO LOAD Ta: 25°C	FULL LOAD I=770mA/48VDC NO LOAD I=13.6mA/48VDC
3	EFFICIENCY(TYP)	95%	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	96.6%

EFFICIENCY vs LOAD



PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	120%-250% RATED OUTPUT POWER	I/P: 53 VDC I/P: 48 VDC I/P: 30VDC O/P: TESTING Ta: 25°C	194%/53VDC 193%/48VDC 180%/30VDC PROTECTION TYPE : Hiccup mode, recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	CH: 28 V-33 V	I/P: NO O/P: MIN LOAD Ta: 25°C	31.9V PROTECTION TYPE : Shut off o/p voltage, clamp by TVS diode
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 53VDC O/P: FULL LOAD Ta: 25°C	NO DAMAGE PROTECTION TYPE : Hiccup mode, recovers automatically after fault condition is removed

Control Function Test

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	REMOTE CONTROL	Power on: 1.2VDC < R.C-com < 12VDC  Power off: R.C-com < 0.4VDC	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	TEST: OK

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : 49 A / 80 V Q2 Rated : 49 A / 80 V	I/P: High-Line +3V = 56V DC ON/OFF VDS: O/P: (1) Full Load (2) Output Short (3) Full Load Continue Ta: 25°C	Q1 VDS: (1) 58.6V (2) 58.6V (3) 57.4V Q2 VDS: (1) 62.1V (2) 62.1V (3) 61.3V
2	Input Capacitor Voltage	C22 Rated: : 105 μ / 100 V	I/P: High-Line +3V = 56 V O/P: (1) Full Load input on/off (2) Min load input on /Off (3) Full Load /Min load Change (4) Full load continue Ta: 25°C	(1) 57.2V (2) 57.2V (3) 57.2V (4) 57.2V
3	Control IC Voltage Test	PWM IC U1 Rated 7.5V-14V	I/P: High-Line +3V = 56V DC ON/OFF O/P(1) FULL LOAD (2) Output Short (3) O.L.P (4) NO LOAD VR 下限.LOW LINE Ta: 25°C	(1) 8.22V (2) 8.14V (3) 8.30V (4) 7.82V

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RADIATION	<input checked="" type="checkbox"/> EN55032 <input type="checkbox"/> EN55011 <input type="checkbox"/> CLASS A <input checked="" type="checkbox"/> CLASS B	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL Test by certified Lab
2	CONDUCTION	<input checked="" type="checkbox"/> EN55032 <input type="checkbox"/> EN55011 <input type="checkbox"/> CLASS A <input checked="" type="checkbox"/> CLASS B	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL Test by certified Lab
3	E.F.T	EN61000-4-4 <input type="checkbox"/> LIGHT INDUSTRY INPUT: 0.5KV <input type="checkbox"/> MEDICAL <input checked="" type="checkbox"/> INDUSTRY INPUT: 1KV	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
4	SURGE	IEC61000-4-5 <input type="checkbox"/> MEDICAL <input type="checkbox"/> LIGHT INDUSTRY L-N : 0.5KV L,N-PE: 0.5KV <input checked="" type="checkbox"/> INDUSTRY L-N : 1KV L,N-PE: 1KV	I/P: 48VDC O/P: FULL LOAD Ta: 25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
5	Test by certified Lab & Test Report Prepare Any contradictions of the test results, please refer to the latest EMC test report			

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																
1	TEMPERATURE RISE TEST	MODEL : NID-35-24 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P : 48 VDC O/P : FULL LOAD Ta= 25.3 °C 2. HIGH AMBIENT BURN-IN : 1.5 HRS I/P : 48 VDC O/P : FULL LOAD Ta= 55.4 °C																																		
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 25.3 °C</th> <th>HIGH AMBIENT Ta= 55.4 °C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>L1</td> <td>58.5°C</td> <td>88.4°C</td> </tr> <tr> <td>2</td> <td>Q1</td> <td>56.2°C</td> <td>86.1°C</td> </tr> <tr> <td>3</td> <td>Q2</td> <td>55.1°C</td> <td>84.6°C</td> </tr> <tr> <td>4</td> <td>ZD1</td> <td>47.6°C</td> <td>77.4°C</td> </tr> <tr> <td>5</td> <td>C32</td> <td>50.7°C</td> <td>80.5°C</td> </tr> <tr> <td>6</td> <td>C23</td> <td>53.0°C</td> <td>83.2°C</td> </tr> <tr> <td>7</td> <td>U1</td> <td>57.3°C</td> <td>86.7°C</td> </tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 25.3 °C	HIGH AMBIENT Ta= 55.4 °C	1	L1	58.5°C	88.4°C	2	Q1	56.2°C	86.1°C	3	Q2	55.1°C	84.6°C	4	ZD1	47.6°C	77.4°C	5	C32	50.7°C	80.5°C	6	C23	53.0°C	83.2°C	7	U1	57.3°C	86.7°C
NO	Position	ROOM AMBIENT Ta= 25.3 °C	HIGH AMBIENT Ta= 55.4 °C																																	
1	L1	58.5°C	88.4°C																																	
2	Q1	56.2°C	86.1°C																																	
3	Q2	55.1°C	84.6°C																																	
4	ZD1	47.6°C	77.4°C																																	
5	C32	50.7°C	80.5°C																																	
6	C23	53.0°C	83.2°C																																	
7	U1	57.3°C	86.7°C																																	
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 48 VDC O/P : 158% LOAD Ta : 25°C	TEST : OK																																
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 20 VDC / 53 VDC O/P : 100 % LOAD Ta= -35°C	TEST : OK																																
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 55 °C /95 %R.H NO DAMAGE	I/P : 56 VDC O/P : FULL LOAD Ta= 55 °C HUMIDITY= 95 %R.H	TEST : OK																																
5	TEMPERATURE COEFFICIENT	±0.03%/°C(0-55°C)	I/P : 48VDC O/P : FULL LOAD	±0.0031%/°C(0-55°C)																																
6	STORAGE TEMPERATURE TEST	-30-105°C	1. Thermal shock Temperature : -45°C~ +110°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : STATIC																																	
7	THERMAL SHOCK TEST	-30-55°C	1. Thermal shock Temperature : -35°C~ +60°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 15cycle: 48 VDC / FULL LOAD AC ON 3sec/AC OFF 1sec TEST 1cycle: 48 VDC / FULL LOAD Burn In Test																																	
8	VIBRATION TEST	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10-500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 3G (5) Test Time : 180min in each axis (X.Y.Z) (6) Ta : 25°C																																	



9	Ongoing Reliability Test	I/P : 48VDC O/P : FULL LOAD TA=50°C Demonstration Mean Time Between Failure : 30,000 hours
---	--------------------------	---

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LIUTT		Wangdz

2018.4.30 GP-A50-F010