



Test Report : SCWN06W8-05

6W DIP Package 8:1 wide Input DC-DC Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5% ~ +1.5 %	I/P:48VDC O/P:FULL LOAD Ta:25°C	-0.71%	P
2	RIPPLE & NOISE	100 mVp-p	I/P:48VDC O/P:FULL LOAD Ta:25°C	10 mV	P
3	LINE REGULATION	-0.5% ~ +0.5 %	I/P:9VDC~75VDC O/P:FULL LOAD Ta:25°C	-0.02% ~ +0.02%	P
4	LOAD REGULATION	-0.5% ~ +0.5%	I/P:48VDC O/P:0% LOAD~FULL LOAD Ta:25°C	-0.17% ~ +0.24%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	79%	I/P:48VDC O/P:FULL LOAD Ta:25°C	79.91%	P
2	DC CURRENT	132 mA / FULL LOAD 5 mA / NO LOAD	I/P:48VDC O/P:NO / FULL LOAD Ta:25°C	128.7 mA / FULL LOAD 3.2 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	CONTINUOUS	I/P:75VDC O/P:FULL LOAD Ta:25°C	CONTINUOUS, AUTOMATIC RECOVERY	P
2	OVER LOAD PROTECTION	110~230%	I/P:48VDC O/P:TESTING Ta:25°C	145.2% HICCUP MODE AUTO-RECOVER	P
3	CASE TEMPERATURE	+115°C max	I/P:48VDC O/P:TESTING Ta: TESTING	OK AUTOMATIC RECOVERY	P
4	OVER VOLTAGE PROTECTION	YES	I/P: 48VDC O/P: MIN LOAD Ta:25°C	PROTECTION TYPE : CLAMP ZEBER DIODES	P
5	UNDER VOLTAGE LOCKOUT	START-UP 8.8V SHUTDOWN OLTAGE 8.0V(Type)	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.12 VDC 7.54 VDC	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:3000 VDC/min	I/P-O/P:3000 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:FULL LOAD Ta=80°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:50% LOAD Ta=95°C												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>57.4°C</td> <td>105.9°C</td> <td>111.3°C</td> </tr> </tbody> </table>			NO	Position	1	2	3	1	CASE	57.4°C	105.9°C	111.3°C
NO	Position	1	2	3										
1	CASE	57.4°C	105.9°C	111.3°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:48VDC O/P: FULL LOAD Ta= -40°C	TEST : OK										

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 2.5 M.T.B.F : 400KHRS		

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG